

PACKAGING



MIXING



APPLICATION



USES



FLOOR



WALL

SUBSTRATES

CONCRETE
BRICK
BLOCK
RENDER WALLS

DESCRIPTION

Quickcrete is a mortar designed for jobs requiring a fast set and high strength. Quickcrete is ready to use, just add water, no other additives required.

USES

- Sealing plumbing pipes
- Setting toilet pans
- Grouting and patching

COVERAGE (approximate)

200 x 10kg bags = m³

PERFORMANCE DATA

Compression Strength 29Mpa (unconstrained)

SPECIFICATION

The fast setting mortar shall be Quickcrete manufactured by Construction Chemicals and shall be applied in accordance with the manufacturer's application instructions.

MIXING

Place water in a suitable mixing container and slowly add powder stirring continually to achieve a stiff paste. Do not mix more than can be used within 10 minutes. Do not use any additives.

POT LIFE

20 mins at 25°C @ 50% R.H.

APPLICATION

Apply mortar with a trowel or similar tool. Do not overwork as this will decrease the product's overall strength. Set time is 15 minutes @ 20°C but will vary according to temperature. Sealing leaks in masonry walls can be done by waiting 5-10 mins after mixing then plugging the hole and holding in position until set.

FIRST AID

Contains cement which may cause irritation. Wear gloves on mixing and application. If swallowed, do not induce vomiting. Give a glass of water and seek medical advice.

CLEANUP

Clean up in water.